



Faster pull down for efficient cooling



Option of PP/SS in a tank



PUF insulation



Low power consumption



Eco-friendly refrigerant



Recessed handle

Technical Specifications

DESCRIPTION	CHBK300MP	CHBK300MS	CHBK400MP	CHBK400MS	CHBK500MP	CHBK500MS
Gross Capacity (Ltr)	301	301	401	401	484	484
Temperature Range	2°C to 8°C	2°C to 8°C	2°C to 8°C	2°C to 8°C	2°C to 8°C	2°C to 8°C
Power Supply	230V/50Hz/1Ph	230V/50Hz/1Ph	230V/50Hz/1Ph	230V/50Hz/1Ph	230V/50Hz/1Ph	230V/50Hz/1Ph
Refrigerant	R134a	R134a	R134a	R134a	R134a	R134a
No of Lids (Nos)	1	1	2	2	2	2
Inner Cabinet	Precoated GI Sheet	SS304	Precoated GI Sheet	SS304	Precoated GI Sheet	SS304
PUF Thickness (mm)	60	60	60	60	60	60
Overall Dimensions (WxDxH) (mm)	1140X670X835	1140X670X835	1440X670X835	1440X670X835	1640X670X835	1640X670X835
Net Weight (Kg)	55	55	65	65	73	73
Wheels/Legs	Heavy Duty Castors	Heavy Duty Castors	Heavy Duty Castors	Heavy Duty Castors	Heavy Duty Castors	Heavy Duty Castors

As a continuing policy of research and development in Blue Star, the design, features, technical specifications are subject to change without prior notice. The product images shown are for reference only and actual products may differ. Values mentioned are under standard tested conditions in lab. Actual performance values may vary with different ambient conditions. Features may vary from model to model.



Scan QR Code - Blue Star Customer Care Mobile App



SMS "SERVICE" to 57575



Download Blue Star Customer Care Mobile App from App Store & Google Play



To know more about Blue Star, visit www.bluestarindia.com, email us at coolingsolutions@bluestarindia.com or SMS 'COOL' to 57575

